

Besides its people, a company's data is one of its most critical assets. Keeping that data stored, accessible and secure has become complex and expensive as companies are faced with massive data growth, increasingly stringent regulatory requirements and distributed environments that can range from across-the-hall to across-the-globe. Overland Storage® recognizes the need for businesses to do more—with less and offers effortless data management and protection solutions. The SnapSAN™ S2000 is an iSCSI SAN appliance designed for businesses with growing storage needs and limited resources to manage their end-to-end storage strategies.

### Simple

The full-featured S2000 offers many standard enterprise capabilities, such as auto-provisioning, mirroring for high-availability and active-active failover, as well as, replication and snapshots for data protection. The plug-and-play architecture, combined with the simple management console and Windows-based wizard driven user interface, greatly simplifies installation and routine maintenance.

### Smart

The SAN Manager software can monitor and manage multiple S2000 storage systems—locally or remotely—using a local windows application or via web browser in heterogeneous environments. The GUI accesses storage event logs and immediately displays any faults. Email Notifications or text events can be sent to system administrators—or even to a remote management organization.

### Automated

Included in the S2000 is the auto-provisioning breakthrough capability, allowing the S2000 to proactively meet growing capacity demands by automatically increasing capacity on the host as needed – without user involvement. The expansion is non-disruptive and works flawlessly without the need for pre-allocating or estimation of unknown storage needs.

### Integrated

The S2000 plugin for the VMware vCenter Server application provides deep integration with VMware ESX platforms, resulting in unrivalled and outstanding support for datacenter virtualization technologies. This enables Overland customers to stretch their investments even further by realizing unparalleled efficiencies in server and storage resource utilization.

### Reliable





Business Continuity plans will keep your organization up and running. A key to this success is a feature-rich solution that provides both mirroring and replication option. With the SnapSAN S2000 you don't have to make the choice between the features you need and the price you can afford. The S2000 also integrates directly into VMware vCenter Server making it one of the easiest management tools on the market. By deploying the SnapSAN mirroring and replication features, you've taken the first step toward your Business Continuity initiatives



### Highlights

- Integrates seamlessly into Windows, Hyper-V, VMware, Linux, UNIX and Mac OS X environments
- Customized SnapSAN plugin for direct integration and management within VMware
- Mirroring option for VMware and Windows Servers + Replication option for Microsoft environments
- Automatically extends storage volumes making capacity instantly available to the organization
- Scales to 192TB with the addition of SnapServer E2000 Expansion Chassis
- VSS provider enabling application consistent snapshots and integration with leading third-party backup products
- Multi-pathing using Windows Multi-Path I/O (MPIO) framework

## Specifications

<b>Initiator OS Support</b>	Windows XP, Windows Vista, Windows 7, Windows Server 2003, Windows Server 2003 R2, Windows Server 2008, Windows Server 2008 R2. Support for VMware ESX 3.5, Update 5 and ESX 4.0, Update 1 Linux: Red Hat Enterprise Linux 4 and 5, SuSE Linux Enterprise 10, Mac OS X 10.5 and 10.6 using ATTO iSCSI initiator, Solaris 10 (Sparc and X86), Novell NetWare 6.5 SP7
<b>Storage Licenses Included</b>	512 Host Connections
<b>Management</b>	Wizard-based Installation, Volume Usage Statistics, Event Log, Email Notification, Administrator Authentication, Remote Management, Multi-Server Monitoring and Visualization with SnapServer Manager
<b>Data Storage - iSCSI SAN</b>	Compliant with iSCSI standard, RFC 3720, Authentication: One-way CHAP / Mutual CHAP, iSNS Server Support, 256 Targets per Appliance, 512 Simultaneous Sessions, Supports SCSI Persistent Reservations
<b>RAID Levels Data Protection</b>	RAID Levels 0, 1, 5, 6, 10, 50 & 60 256 Snapshots per Appliance, OS agnostic replication support for Windows, Mac OS X, Linux, UNIX, VMware,
<b>Snapshot &amp; Replication</b>	VSS Provider for Windows
<b>High Availability - Mirroring</b>	Active/Active Failover, Support for Mirroring on Windows Server (2003 R2, 2008 & 2008 R2) and VMware ESX (3.5 & 4.0)
<b>CPU &amp; Memory</b>	Intel Xeon E5504 Quad-Core Nehalem CPU, 2GB DDR3 1333MHz Registered DIMMs
<b>Windows Support</b>	One-step Provisioning, Integrated Auto Provisioning, VDS and VSS Providers, MPIO Support, Microsoft Cluster Server Support, Microsoft Hyper-V Support
<b>VMware Support</b>	Overland S2000 SAN plugin for VMware vCenter Server application allows you to manage S2000 from the vCenter client application, Enhances use of VMware HA, VMotion and DRS, Continuous access to your Datastores
<b>Drive Configuration</b>	12 x 1TB 7200 RPM SATA II Drives (12TB raw capacity), or 12 x 2TB 7200 RPM SATA II Drives (24TB), or 12 x 600GB 15000 RPM SAS Drives (7.2TB)
<b>Network Interface</b>	2 Gigabit Ethernet Ports included, Dual Port Gigabit Ethernet Card - PCIe (option available), Quad Port Gigabit Ethernet Card - PCIe (option available)
<b>Expansion Array Interface</b>	Includes external Serial Attached SCSI (SAS) port for expansion, Supports up to 7 SnapServer EXP E2000 units
<b>Physical/Mounting</b>	Width: 17.2" (437mm), Height: 3.5" (89 mm) 2U, Depth: 25.5" (648 mm), Weight: 55 lbs , 19" rack mount slide rails included Minimum rack depth 32" (812.8mm)
<b>Agency Approvals</b>	CE, cULus, FCC Class A, CE, VCCI    
<b>Power</b>	800W auto ranging, hot swappable modules (1+1 Redundant), 100-240VAC, 50-60Hz, 10 - 4 Amp\
<b>Power Consumption</b>	Idle: 255W / 2.27Amps; Peak: 263W / 2.32Amps
<b>Environmental Limits</b>	Operating Temperature Range: 10° C to 35°C (50° to 95° F), Operating Humidity Range: 8% - 90% non-condensing Operating Altitude: -200 ft. to 10,000 ft. (0m to 3,048m)
<b>Included with Unit</b>	2 x Cat5 Ethernet cables, Custom 19" rack-mount slide rails, Power Cords for US, UK & EU
<b>Standard Warranty</b>	The SnapSAN S2000 is covered by a three-year OverlandCare limited hardware and software warranty including Next Business Day Advance Parts Replacement support and 24x7 telephone support. SnapSAN S2000 systems are eligible for enhanced maintenance options to augment the standard limited warranty. Support coverage of all expansion units and software options must be purchased separately and run concurrently with the primary unit. For full details of all of our service programs, please contact your preferred authorized reseller or contact Overland Storage directly at +1 (858) 571-5555.



## Sales Offices

**North America**  
125 S. Market Street  
San Jose, CA 95113  
USA  
Tel: 800.729.8725

**Asia Pacific**  
Level 44, Suntec Tower 3  
8 Temasek Boulevard  
Singapore, 038988  
Tel: +65.6866.3848

**France**  
88 ter avenue du Général Leclerc  
92100 Boulogne Billancourt  
France  
Tel: +33.17431.1070

**Germany**  
Wilhelm Wagenfeld Straße 28  
80807 München  
Germany  
Tel: +49.89.329890.800

**United Kingdom**  
Ashville Way  
Wokingham, Berkshire  
RG41 2PL England  
Tel: +44 (0) 118.989.8000



[www.overlandstorage.com](http://www.overlandstorage.com)

©2010 Overland Storage. All trademarks and registered trademarks are the property of their respective owners. The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. Overland Storage shall not be liable for technical or editorial errors or omissions contained herein.

S2000-DS1010-01